

CertaUPS

C60 800VA - 2000VA

Line interactive

Compact and ideal for smaller backup power requirements - CCTV, EPOS, small office hardware, security systems and PC workstations.

The C60 range is one of the most practical and compact UPS solutions available.

Compatible with most operating systems, the intuitive monitoring software provides safe shutdown in the event of an extended power failure with the UPS automatically restarting when power is restored.



Line interactive (VI) technology



USB connectivity



C60 800VA - 2000VA

Product Specification

| MODELS | C60-800 | C60-1000 | C60-1500 | C60-2000 |
|-----------------------------|--|-----------------|--|-----------|
| Power (VA) max | 800 | 1000 | 1500 | 2000 |
| Power (W) max | 480 | 600 | 900 | 1200 |
| INPUT | | | | |
| Input Voltage | 220/230/240VAC | | | |
| Acceptable Input Voltage | 162-290VAC | | | |
| Input Frequency | 50/60Hz (Auto Sensing) | | | |
| OUTPUT | | | | |
| Voltage Regulation | +/-10% (Battery Mode) | | | |
| Frequency Regulation | +/-1Hz (Battery Mode) | | | |
| Transfer Time | Typical 2-6ms; 10ms max | | | |
| Waveform | Simulated Sinewave (Battery Mode) | | | |
| PROTECTION | | | | |
| Full Protection | Overload, Battery Discharge and Overcharge Protection | | | |
| DISPLAY | | | | |
| LCD Display | AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault & Battery Low | | | |
| FEATURES | | | | |
| Usable Features | Off-Mode Charging, AVR, Auto-Restart, Cold Start, USB, RJ11 & 45 Filters, LCD Display | | | |
| BATTERY | | | | |
| Runtime | 3 minutes | 4 minutes | 3 minutes | 2 minutes |
| Charging Time | 4-6 hours recovery to 90% | | | |
| MECHANICAL | | | | |
| Dimensions W x D x H (mm) | 100 x 285 x 142 | 146 x 350 x 160 | 146 x 397 x 205 | |
| Net Weight (Kg) | 4.9 | 8 | 11.1 | 11.5 |
| Battery Protected Outputs | 3 | 3 | 5 | 5 |
| Surge Protected Outputs | 1 | 1 | 1 | 1 |
| AC Outlets | 3 x IEC C13, 1 x Surge Protected IEC C13 | | 5 x IEC C13, 1 x Surge Protected IEC C13 | |
| ENVIRONMENT | | | | |
| Operating Temperature Range | UPS: 0°C - 40°C, Batteries: 20 - 25°C | | | |
| Humidity | 0-90% Relative Humidity (Non Condensing) | | | |
| SOFTWARE | | | | |
| Connection | USB Connectivity | | | |
| Operating System Supports | Windows 2008/7/8/10 Linux/Unix and MAC | | | |

Full technical specification and product information can be found at www.certaups.com